

Application
The Tension Clamp is used for ADSS is mainly used to connect terminal support, tension support and splice support in setting up ADSS.

Description
The tension clamp made of aluminum clad steel or aluminum alloy with firm grit applied and the individual rod assembled into groups to increase the strength of tension clamp in the condition of decreasing the stress imposed on cable.



Features
Easy installation and no special tools needed.
It is compatible with other hardware.
Right-hand lay direction standard.

Catalogue lists

Table G2 Heliacal Dead End Clamp for ADSS short span not more than 150m

Catalog No.	Suitable Dia. (mm)	Length (mm)	Weight (mm)	Color Code
DCC-0800/AD	7.70-8.30	700	0.2	Black
DCC-0910/AD	8.31-8.30	740	0.3	Blue
DCC-0940/AD	8.90-9.90	820	0.3	Orange
DCC-1039/AD	9.91-10.87	820	0.3	Black
DCC-1126/AD	10.88-11.64	860	0.3	Green
DCC-1207/AD	11.65-12.49	900	0.4	Yellow
DCC-1288/AD	12.50-13.26	940	0.4	Red
DCC-1371/AD	13.27-14.15	980	0.5	Black

Table G3 Heliacal Dead End Clamp for ADSS Excess short span not more than 80m

Catalog No.	Suitable Dia. (mm)	Length (mm)	Weight (mm)	Color Code
DCC-0825/ADE	7.35-8.25	560	0.1	Red
DCC-0926/ADE	8.26-9.26	600	0.1	Green
DCC-1039/ADE	9.27-10.39	630	0.2	Yellow
DCC-1168/ADE	10.40-11.68	670	0.3	Blue
DCC-1311/ADE	11.69-13.11	730	0.3	Orange